Aluminum Brightener

#### **SECTION I - IDENTIFICATION**



House of Chemicals 304 N Chadbourne St San Angelo, TX 76903 (325) 655-8376

CHEMTREC :..... (800) 424-9300

Product Number 4013

Product Name Aluminum Brightener

**Chemical Family** 

CAS Number Multiple
Date Prepared 3/5/2015
Revision Number 9/14/2020

Recommended Use Industrial Use Only

# **SECTION II - HAZARDOUS IDENTIFICATION**

## **GHS CLASSIFICATION:**

# Classification

Corrosive to Metals Category 1

Skin Corrosion/Irritation Category 1A, B, C

Serious Eye Damage/Eye Irritation Category 1

# **DANGER!**

#### **GHS LABEL:**



## **Hazard Statements**

H290 May be corrosive to metals

H314 Causes severe burns and eye damage

H318 Causes serious eye damage

# Aluminum Brightener

#### **Precautionary Statements**

P234 Keep only in original packaging

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash... thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+361+353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water or

shower.

P304+340 IF INHALED: Remove victim to fresh air and keep comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and

easy to do so - continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

P321 Specific treatment (see ... on this label).

P363 Wash contaminated clothing before reuse.

p390 Absorb spillage to prevent material damage.

P405 Store locked up.

P406 Store in a corrosive resistant/... container with a resistant inner liner.

P501 Dispose of contents/container to...

#### SECTION III - COMPOSITION/INFORMATION ON INGREDIENTS

The precise composition of this product is proprietary information. In the event of a medical emergency, a complete disclosure will be provided to medical personnel.

| Component Name      | CAS#      | Component% | OSHA PEL          | ACGIH TLV         |
|---------------------|-----------|------------|-------------------|-------------------|
| Sulfuric Acid       | 7664-93-9 | 20         | 1 mg/m³ (Ceiling) | 1 mg/m³ (Ceiling) |
| Ammonium Bifluoride | 1341-49-7 | 13         | 2.5mg/m³          | 2.5mg/m³          |

#### **SECTION IV - FIRST AID MEASURES**

**Contact with eyes:** Flush with water for 15 minutes. Seek immediate medical attention.

**Skin contact:** Wash exposed areas with water and mild soap. Remove contaminated clothing

immediatelyand launder before reuse. If irritations persist, seek immediate medical

attention.

**Inhalation:** Remove victim to fresh air. Administer oxygen or artificial respiration if breathing is

affected or stopped. Seek immediate medical attention.

# Aluminum Brightener

**Ingestion:** If swallowed. Do not induce vomiting. Seek immediate medical attetntion.

#### **SECTION V - FIREFIGHTING MEASURES**

**Suitable Extinguishing Media:** Water fog, foam, CO2, dry chemical.

Special Fire Fighting Procedures Use self-contained breathing apparatus and full bunker gear in fire areas.

Evacuate all unprotected personnel from area. Keep containers cool with water fog to minimize swelling taking care not to spread flames with water

used for cooling.

**Unusual Fire Fighting Hazards:** Contact with reactive metals can generate hydrogen gas, which is flamable.

Water mixed with acid evolves extreme heat and can cause spattering.

#### **SECTION VI - ACCIDENTAL RELEASE MEASURES**

**Personal Precautions:** Evacuate all unprotected personnel from the area.

**Environmental Precautions:** Contain spill if it can be done with minimal risk. Prevent liquid from

entering drains, sewers or waterways. Notify proper authorities.

**Methods for Cleaning Up:** Cover with sodium bicarbonate or a soda ash/slaked lime minture

(50/50). Mix and add water if necessary to form a slurry and complete neatralization. Scoop up slurry and wash site with soda ash solution.

#### **SECTION VII - HANDLING AND STORAGE**

**Handling and Storage:** • Keep cont

- Keep containers tightly closed when not in use.
- If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional ventilation or exhaust systems may be required.

#### SECTION VIII - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

#### **EXPOSURE LIMITS:**

| Component Name      | CAS#      | OSHA PEL          | ACGIH TLV         |
|---------------------|-----------|-------------------|-------------------|
| Sulfuric Acid       | 7664-93-9 | 1 mg/m³ (Ceiling) | 1 mg/m³ (Ceiling) |
| Ammonium Bifluoride | 1341-49-7 | 2.5mg/m³          | 2.5mg/m³          |

Engineering Controls: Adequate local or mechanical ventillation to reduce vapor or mist to below

the PEL or TLV.

**Monitoring:** Follow accepted work practices for handling a corrosive material.

#### Personal Protective Equipment (PPE)

# Aluminum Brightener

**Eye Protection:** Goggles or approved OSHA device with side shields; do not wear contact

lenses when handling this product.

**Skin Protection:** Impervious solvent resistent gloves. Impervious apron and work boots

recommend where splashing may occur.

Respiratory Protection: Use the proper respirator in areas where the chemical exposure is

unknownor above the OSHA PEL or ACGIH TLV.

| SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES |                               |  |
|---|-------------------------------|--|
| Appearance                                    | Clear to slightly hazy liquid |  |
| Odor  | Sulfuric odor                 |  |
| pH@25°C                                       | 1.0 - 2.0 (1% in water)       |  |
| Melting/Freezing Point                        | No Data Available             |  |
| Flashpoint                                    | No Data Available             |  |
| Specific Gravity                              | 1.836                         |  |
| Soluability                                   | Soluable                      |  |
| Auto-Ignition Temperature                     | No Data Available             |  |
| Decomposition Temperature                     | No Data Available             |  |
| VOC Content                                   | No Data Available             |  |
| Odor Threshold                                |                               |  |
| Boiling Range                                 | 530°F                         |  |
| Evaporation Point                             | < 1 (Butyl Acetate = 1)       |  |
| Flammable Limits - Upper                      | No Data Available             |  |
| Flammable Limits - Lower                      | No Data Available             |  |
| Vapor Pressure                                | < 1 mmHg @ 20°C               |  |
| Vapor Density (Air=1)                         | 3.4                           |  |
| Viscosity                                     | No Data Available             |  |

#### **SECTION X - STABILITY AND REACTIVITY**

Stability: Stable

Conditions to Avoid: Material is very corrosive and will attack most metals and

evolve hydrogen gas.

Hazardous Decomposition/Byproducts: Reaction with reactive metals may produce flammable

hydrogen; reaction with bases can be violent and produces

extreme heat.

Hazardous Polymerization: Will not occur.

Polymerization Conditions to Avoid: None

Incompatibilities: Strong Oxidizers and bases

Metals

# Aluminum Brightener

## **SECTION XI - TOXICOLOGICAL INFORMATION**

**Likely Route of Exposure:** Contact and inhalation; ingestion possible.

**Inhalation:** Can cause damage to nasal and respiratory passages.

**Eye Contact:** Will cause severe burns on contact and will damage the eyes.

**Skin Contact:** Causes burns, possible deep ulceration.

**Ingestion:** Causes severe damage to mucous membranes and deep tissues, a

result in death on penetration to vital areas.

**Acute Toxicity Value:** See Health Hazards below.

**Chronic (Long Term) Effects:** See Health Hazards above.

# **Toxicity:**

| Component Name      | LD50                    | LC50  |
|---------------------|-------------------------|---|
| Sulfuric Acid       | Oral - rat - 2140 mg/kg | Inhalation - mouse - 320 mg/m3/2H; Inhalation - rat - 51- |
| Ammonium Bifluoride | Not Established         | Not Established   |

**Reproductive Effects** Not Applicable

**Teratogenicity** Not Applicable

Mutagenicity Not Applicable

**Embryotoxicity** Not Applicable

Sensitization to Product Not Applicable

Synergistic Products Not Applicable

**Carcinogenicity** Not Applicable

#### **SECTION XII - ECOLOGICAL INFORMATION**

**Ecotoxicity:** Information not available.

**Mobility:** Information not available.

# Aluminum Brightener

**Degradability:** Information not available.

**BioAccumulation:** Information not available.

# **SECTION XIII - WASTE DISPOSAL CONSIDERATIONS**

Follow Federal, state, and local regulations.

#### **SECTION XIV - TRANSPORT INFORMATION**

## **DOT SHIPPING INFORMATION**

Proper Shipping Name: Sulfuric Acid

Contains:

Hazard Class and Label: 8

Identification Number: UN1830

Packaging Group:

Other Shipping Info:

## **SECTION XV - REGULATORY INFORMATION**

TSCA STATUS:..... The components of this product are listed on the TSCA Inventory

## SARA TITLE III SECTION 302/304 EXTREMELY HAZARDOUS SUBSTANCE:

| Component Name | CAS#      | % by wt. | RQ (lbs.) | TPQ (lbs.) |
|----------------|-----------|----------|-----------|------------|
| Sulfuric Acid  | 7664-93-9 | 20       |           | 1,000      |

# SARA TITLE III SECTION 311/312 HAZARD CATEGORIZATION:

| Acute | Chronic | Fire | Pressure | Reactive |
|-------|---------|------|----------|----------|
| Χ     | X       |      |          | Х        |

# **SARA TITLE III SECTION 313 SUPPLIER INFORMATION:**

No chemicals in this material are subject to the reporting requirements.

## **CERCLA SECTION 102(a) HAZARDOUS SUBSTANCE:**

| Component Name     | CAS#      | % by wt. | RQ (lbs.) |
|--------------------|-----------|----------|-----------|
| Sulfuric Acid      | 7664-93-9 | 20       | 1,000     |
| Ammonium iflouride | 1341-49-7 | 13       | 100       |

# Aluminum Brightener

# **CALIFORNIA PROPOSITION 65:**

No chemicals in this material are subject to the reporting requirements.

| SECTION XVI - OTHER INFORMATION |                                |  |  |  |
|---------------------------------|--------------------------------|--|--|--|
| HMIS Health: 3                  |                                |  |  |  |
| HMIS Flammability: 0            |                                |  |  |  |
| HMIS Reactivity: 2              |                                |  |  |  |
| Additional:                     |                                |  |  |  |
| Specification Information       |                                |  |  |  |
| Department issuing data sheet:  |                                |  |  |  |
| Email address:                  | houseofchemicals1965@gmail.com |  |  |  |
| Training necessary:             |                                |  |  |  |
| Disclaimer:                     |                                |  |  |  |
|                                 |                                |  |  |  |